


# Instruction manual

## MAD with EDS-2



## Pump-Controller :

### Pressure regulation System for Pumps

MAD-EDS-2 Software version 2012.....

<b>Table of contents</b>	<b>Page</b>
1. Safety Precautions	2
2. General / Mode of Operation	4
3. Installation and Mounting	5
4. Wiring and Connections	6
5. Keys and Display	9
6. Display Functions and Initial Settings	11
7. Operating Indicators / menu / Startup	12
8. Trip history monitor	13
9. Expert mode	16
10. Clear presentation of the menu structure MA	18
11. Customer Settings	18
12. Technical execution, terminal diagram, schematic of the respective controller	

# 1. Safety Precautions

Before installing and commissioning of the pump controller, please read the product manual carefully and observe all warnings and safety instructions. Keep this manual is always easily accessible in the vicinity of the frequency converter controller.

## Definition of Information



### Warning!

In disregard of the safety instructions may lead to serious and life-threatening bodily injury or property damage occur, a significant!



### Caution!

Failure to observe these instructions may lead to serious and life-threatening bodily injury or property damage occur, a significant!



### Notice!

Failure to observe these instructions may lead to malfunction of the plant!



### Warning!

The frequency inverter controller generates dangerous electrical voltages and controls potentially dangerous rotating mechanical parts.



### Warning!

The installation, Initial Settings and maintenance of these drives can only be by qualified personnel who are familiar with the operation, carried out.



### Warning!

The frequency inverter controllers have the lead after the mains off dangerously high voltage. Wait, therefore, after switching off the mains for at least 5 minutes before you work on the device. It is important to ensure that no live parts are touched, or when voltage is applied between the capacitors are charged. Do not work on the wiring and make sure no signals when voltage is applied.



### Caution!

All pump controllers are tested for dielectric strength and insulation resistance. Be disconnected before the isolation measurement on the pump unit, for example, as part of the inspection, the frequency control!



Warning!

**Warning!**

The drive - controller has a leakage current. Ground the frequency - Controller at the designated ports.

The customer's RCCB must be an in-MAH, MAS2, MAK, MAE - dial to pole sensitive / selective RCCB tripping with type B be 300 mA.

The customer's RCCB must be a the MAI, MAD, MAG - dial to pole sensitive RCCB type B with his tripping 30 mA. It is recommended to secure the separate frequency - control.

Observe the regional regulations for electrical installation!



Warning!

**Warning!**

Make sure that the input voltage corresponds to the nameplate voltage registered.



Caution!

**Caution!**

Environmental conditions such as high temperatures, high humidity should be avoided as well as dust, dirt and corrosive gases. The installation should be a well-ventilated and not exposed to direct sunlight location.



Caution!

**Caution!**

Do they no mains power to the sensor terminals or to the control terminals.

**Caution!**

Enter the operating signals START / STOP button on the control panel on or about the triggering of the external contacts and not by turning on and off a mains or motor contactor.



Caution!

**Caution!**

It is strongly recommended that all electrical equipment conforms to the National Electrical Codes and local regulations. Only qualified personnel should perform installation, alignment and maintenance. The manufacturer reserves the right to alter the technical data in order to make improvements or update information.



Notice!

**Notice!**

The technical data and descriptions in this guide are correct to the best knowledge and belief. Technical improvements have been continuously carried out - that's why the manufacturer reserves the right, without prior notice to carry out such changes.

The manufacturer can not be held liable for errors in the manual.

Warranty is within Germany and within the incorporated statutory warranty period and applies only to the product itself and not for any consequential loss or damage or costs associated with the occurrence of a Warranty claim arise at other plants or plant parts. The operator shall, in each case to ensure that a failure or defect in the product can not lead to further damage.

## 2. General / Mode of Operation

### 2.1 MA .... Pressure Control System

Congratulations on purchasing this high-quality pump control. This product complies with the latest technology and is continually developed and improved. The device was subjected to the production of an extensive examination and therefore functions properly. To read to ensure optimal function and observe these operating instructions.

This frequency inverter controller operates as an automatic pressure regulator, tested. The speed of the pump (s) will be adjusted continuously. The actual pressure in the system is determined by pressure transducer (sensor). A PI controller regulates the pressure by analogy.

The pressure regulator is programmable and can be adapted to the respective operating conditions. The parameters are displayed on the display in plain text. Commissioning is menu driven. During commissioning, some data must be entered to ensure the smooth operation of the pumping plant. An adjustment of specific parameters (expert mode) requires special knowledge of pump technology. This should be done by a competent person or the manufacturer.

### 2.2 Benefits of speed control:

- almost constant pressure
- Continuous adjustment of pump power to the changing operating conditions
- Energy saving
- a speed-double unit replaces a four-fold pressure switch system
- low mechanical wear of the pumps
- Maintenance

### 2.3 Principles of pressure control

To operate a speed control can be accurately and effectively, the following points to consider:

- the pump (s) must be construed in accordance with the plant / Requirement
- the pump (s) shall have power reserves available (80. .90%) = system reserve capacity at rating
- with submersible pumps must be based on an output reduction of about 5. .10%

### 2.4 Construction of a pressure control system


Non-return valve preventer is imperative and must be in the pressure behind the Pump will be installed! The expansion tank is to be fitted if required.




Caution!

- |                    |                       |
|--------------------|-----------------------|
| 1 Flow direction   | 2 Controller          |
| 3 Motor            | 4 Pump                |
| 5 Non-return valve | 6 Pressure Transducer |
| 7 Pressure vessel  |                       |

Example 1 pump System



Example 2 pumps System



## **2.5 Note for the operation of the system with Pressure vessel!**

If the plant is operated with a pressure vessel, the vessel must be pre-pressed in normally state. The pre-squeezing pressure should be checked regularly. The amount of pre-squeezing pressure is: Start pressure bar minus 0.20.

e.g.:	Nominal System Pressure:	4.00 bar
	Vessel Air Pressure:	3.80 bar

## **2.6 Booster Sets**



Notice!

Booster units are ready plumbed and wired pump installations. For them, the installation cost is minimal - connect to the existing network of pipes, mains and commissioning. The regulator is factory set at these facilities.

This manual refers only to the electrical control of the system is therefore possibly the pump consult the manual (s) note the / partition.

See manufacturers data sheet.

## **3. Installation and Mounting**

Environmental conditions such as high temperatures, high humidity should be avoided as well as dust, dirt and corrosive gases. The installation should be a well-ventilated and not exposed to direct sunlight location.



Caution!

Because of convection, the frequency control during installation of at least Be installed 15 cm from side walls or other facilities.



Warning!

The allowable temperature range of +5 ° C to +30 ° C must not be under-or exceeded.

Do not install the Inverter controller near heat-radiating bodies.

### **3.1 Mounting the MA.... Controller**

Metal box:

In the rear contains holes for wall mounting of the cabinet.  
The sole assembly recommended hung stud to the electrical cabinet.

Mounting Dimensions: See manufacturers data sheet MAD.

## 4. Wiring and Connections



Warning!

**Make sure that the input voltage corresponds to the nameplate voltage registered.**



Caution!

**Be sure to supply voltage and terminal assignment instructions!**

The installation, commissioning and maintenance of the actuators may be of an expert who is familiar with the pump system will be implemented.



Warning!

**Do they no mains power to the sensor - or control terminals.**

No manipulation of the sensor signal to make!

No other users connect to the 24V supply!

**The used pressure sensor** (0. .10 V) or (4. .20 mA),  
is connected to the respective terminals!

The respective pin assignment, refer to the respective diagram.



Notice!

**In systems with several pumps** are used again and 0. .10 V sensors.

Here you can optionally one or more sensors are connected.

The respective pin assignment, refer to the respective diagram.



Caution!

**Notice!**

If the motor cable longer than 100 meters, it is advisable to install an motor reactor.

**Caution!**

**Verify the correct connection of the network, sensor, and control lines.**

### 4.1 Motor Protection


The MAD - EDS-2 has a monitoring role for the motor current.

The motor current is set on the motor protection relay or soft starter.

As a special version thermistor to monitor temperature can be used.

Contactor

Soft Starter 3RW40



### 4.2 Connection of inputs / outputs


The lower part of the cubicle MAD is the terminal strip.

The line to the pump, the sensor line and the lines for the external contacts will be connected to appropriate wires. Screening is not required.


Only with proper installation, trouble-free operation is guaranteed!

### 4.3 Wiring diagram EDS-2 module

#### 1- pump unit



#### 2- pumps unit




### 4.4 Terminals

When power supply, alarm relay, relay (option), external inputs (option), external outputs (option), sensor (s), pump (s), they face each diagram or schematic or picture of each terminal controller: MAD, MAG on.


#### 4.5 Power Supply

Clamp	Function	Description
<b>PE</b>	<b>Power Supply</b>	PE Ground
<b>L1</b>		L1 Phase
<b>L2</b>	<b>400V AC</b>	L2 Phase
<b>L3</b>		L3 Phase
<b>N</b>		N Neutral
or:		
<b>PE</b>	<b>Power Supply</b>	PE Ground
<b>L1</b>		L1 Phase
<b>N</b>	<b>230V AC</b>	N Neutral




#### 4.6 Port for the alarm relay

Function	Description
Potential-free contact	AL 1 (17)
<b>Register relay</b>	contact AL 2 (18)
230V 1 A	contact AL 3 (16)




#### 4.7 Port for the Run relay

Function	Description
Potential-free contact	contact 4 (24)
<b>Register relay</b>	contact 6 (26) Run Signal (Option)



#### 4.8 Port for the external inputs MAD/G

Clamp	Function	Description
7 / 13	low water / external On /Off	Ext. 34
10	Start/Stop/Reset	(only MAG) Ext. 25
10	Reset	(only MAD) Ext. 25
81	Reference voltage	P24 VDC +
87	Reference voltage	OI VDC -
18 / 82	PTC	(Option) Kaltleiter 1
38 / 82	PTC	(Option) Kaltleiter 2



#### Caution!

Use shielded cable and connect it to the grounding clamps in the cabinet! The maximum length of the control lines may not exceed 20 meters.

Ext. 34: Alarm external Input

Ext. 25: external input

Ext. 25: external input


„Low water“.

„Limit function“.

„Reset“.

(only MAG)

(only MAD)



#### 4.9 Port for the transducer

Funktion	Description	Reference voltage	P24 VDC +
Reference voltage L	VDC -		
Transducer signal	OI	4-20mA	


#### Caution!

Use shielded cable and connected to the grounding clamps in the cabinet!

Note terminal assignment (see the sensor Type plate)!

#### 4.10 Port for the motor / pump

Clamp	Function	Description
U	3 phase motor	U1
V	see the	V1
W	Type plate	W1




#### Caution!

Motors must be connected corresponding the output voltage (230V or 400V): Star- or Delta- connection (motor terminal board)! Output voltage = input voltage.

#### 4.11 Port for the motor / pump: single Phase

Clamp	Function	Description
U	3 phase motor	U1
V	see the	V1



#### Caution!

Verify the correct connection of the network, transducer, and control lines.

Check before switching on the mains again all connections are correct!

#### 4.12 Frequent installation failures












- Sensor is connected wrong
- Sensor is not installed in the pressure pipe behind the non-return valve
- Non-return valve is not installed or not installed in the right direction
- Pipes/pumps are not ventilated
- Wrong running direction
- Motor terminal board is connected wrong (output voltage! Star- or Delta- connection?)

For faults please the notes under 9.2. Troubleshooting note!

## 5. Panel Description

### 5.1 Block rocker and rotary switches

(Rocker, which is above gray side is active!)

1+2		1-2	Rocker:	1+2	1-2
Alarm		OFF	Rocker:	Alarm	OFF
Test		OFF	Rocker:	Test	OFF
DS		DY	Rocker:	DS	DY
		A	Rotary switch A:	Target	ON
		B	Rotary switch B :	Target	OFF
		T	Rotary switch T:	Run On Time	0-10 bar / 25 bar (depending Transducer) 0-10 bar / 25 bar (depending Transducer) 0-30 sec. (5-30 sec.)
		P1	Lamp P1:	Pump 1 on	Run
		P2	Lamp P2:	Pump 2 on	Run
		Alarm	Lamp Alarm:	Alarm active	
		Reset	Reset button:	Alarm Reset	

**Relay K1: P1 pump switches, relay K2: P2 pump switches, alarm relay: switches at fault**

### 5.2 Rocker: Mode 1 + 2 / 1-2

This switch sets the operating mode of the system

- 1+2: Operation of the system with a base load and peak load pump.  
In this mode, the pump with rotary switch "A" one-connected with rotary switch "B" off.  
With the rotary switch "T" they set the delay time. The Pump is changed after each run.  
The second pump is switched on automatically as needed
- 1-2: Operation of the system with base-load pump.  
In this mode, the base-load pump with rotary switch "A" with rotary switch on and "B" switched off.  
With the rotary switch "T" they set the delay time. The Pump is changed after each run.  
The second pump is not switched on. Automatic Switchover in case of failure on the other pump.

### 5.3 Rocker: Alarm ON / OFF

This switch set the alarm mode. "Water shortage"

If the alarm is "ON" is switched to the alarm relays to "water shortage".  
The pressure monitoring, which is active after the fill mode is, 50% of engaging and delayed by **3 minutes** for the off!



#### Dry Run!

If the shift switch "dry run" is active, turn the power off whenever the system pressure of 0.5 bar is not reached in 60 seconds.

#### Fill mode!

If the system is switched "power on" is the lack of water only active if the pumping station has been turned off for the first time to the set pressure.

If the alarm is OFF, the alarm relays to "water shortage" is not turned off  
The "OFF" is used in fire-fighting operation to prevent a shutdown of the pumps.  
Alarm relay does not switch at fault..

### **Rocker: Alarm ON / OFF**

This switch set the alarm mode. "**Switching**"



#### **Fault switching!**

**The pump system is monitored for switching game! Each pump is designed for switching up to 60 times per hour.**

If the alarm is "ON" is switched to the alarm relays to "Fault switching".

The alarm relay switches when the fault

If the alarm is OFF, the alarm relays to "Fault switching" is not turned off.

The "OFF" is used in fire-fighting operation to prevent a shutdown of the pumps.  
Alarm relay does not switch at fault..

### **5.4 Rocker: Test ON / OFF**

This switch set the **24-hour test** run.

This function is used to prevent the pump and one to prevent.  
This function is set to fire-fighting operation.

### **5.5 Rocker: DS / DY**

This switch sets the operating mode of the system

**DS:** Operation of the system with air tank ( pressure switch).

In this mode, the pump on the rotary switch "**A**" is turned on and to dial "**B**" switched off.

With the rotary switch "**T**" they set the Run on Time. The pressure vessel is in pre-pressed at 0.5 bar above cut-in.

The pump is changed after each run. The second pump is automatically switched on as needed or switched at fault.

**DY:** Operation of the facility without pressure vessels (Dynamic mode).

In this mode, the pump on the rotary switch "**A**" is turned on and off to turn "**B**" in promoting zero.

With the rotary switch "**B**" is the switch-off (0.1 - 1 bar).





With the rotary switch "**T**" they set the Run on Time.

The pump is changed after each run. The second pump is automatically switched on as needed or switched at fault.

## 6. Applications





Single pump system or a double pump system **with** expansion tank, alarm and test run

### 6.1 Pressure switch operation

1+2		1-2	Operating mode	1+2	1-2
Alarm		OFF	Alarm Mode Select	ON	OFF
Test		OFF	Test Run Enable	ON	OFF
DS		DY	DS – Stop operation	DS	----
		A	Rotary switch A: Target	ON	z.B. 2,5 bar
		B	Rotary switch B: Target	OFF	z.B. 4,5 bar
		T	Rotary switch T: Run on Time	0-30 sec.	z.B. 3,0 sec.

Single pump system or a double pump system **with no** expansion tank, alarm and test run "OFF"

### 6.2 Dynamic switch Operation

1+2		1-2	Operating mode	1+2	1-2
Alarm		OFF	Alarm Mode Select	ON	OFF
Test		OFF	Test Run Enable	ON	OFF
DS		DY	DS – Stop operation	----	DY
		A	Rotary switch A: Target	ON	z.B. 1,5 bar
		B	Rotary switch B: Target	OFF	z.B. 0,3 bar
		T	Rotary switch T: Run on Time	5-30 sec.	z.B. 10,0 sec.



Lock off: The settings are adjustable  
Bridge 30/31 (yellow) is open.



Lock on: The settings are not adjustable  
Bridge 30/31 (yellow) is closed.

## 7. Switching / operation / start messages

### 7.1 General operation of the EDS-2



Notice!

The pump control MA .... EDS-2, by setting various functions and operational parameters in individual cases can be optimally adapted to all possible operating conditions. The unit is preset at the time of delivery to keep the cost of commissioning local minimum. To set the necessary data to any operating parameters, a switch can be changed. The menu items are invoked as described above. For each parameter is a setting in which either select an option or a value range can be adjusted.

### 7.2 Conditions for starting the MA .... Control

Before control is put into operation the following requirements must be met:

- System / pump suction and discharge side connected to the pipeline!
- Piping and pumps are filling!
- Electrical connection is made and checked!

### 7.3 First turn on the MAD-EDS-2


#### **Caution!**

When the alarm to "Off" are lack of water protection and Switching cycle monitoring is not active! The protection system must be external!

#### **Caution!**

When the alarm to "on" position is the only active when water protection the pump station for the first time has stopped in the pressure (fill mode)!

#### **MAD-Switch EDS-2!**



The EDS-2 reports for **you!** turning the main switch / line voltage with the inset:

**The following message appears on the display:**

```
Custom text
Custom text
00000 RH 00000 RH
Version: 200XXXXX
```

## 8.Operation indicators / Commissioning


### 8.1 MAD-EDS2 into operation

The EDS2 logs after the **startup screen!** with the main picture:

The rotary switches **A, B, T** on the EDS-2 set.




The pump / pump by switching on the **"manual mode"** to "turn" position.



**Check direction of rotation!**

If the wrong direction: switch network, replace two phases. **Control!**

If the rotational direction is correct, switch to **"automatic mode"** position.



In automatic mode, the pumps - the pressure regulator automatically according to the sensitivity. Important: **check!**

Caution! In manual mode, the pump runs continuously.

Caution! In manual mode, there is no protection!



Caution!

## 8.2 Operation indicators on the display EDS-2

After the main switch / voltage of the operational data in the display appear:

Startup message for 20 sec.:

<p>Custom text Custom text 00000 RH 00000 RH Version: 200XXXXX</p>	<p>Startup screen when you turn for 20sec. Custom text RH–(Run Hour) Operating hours for each pump Software Version: Year, month, day</p>
<p>00,5 ON : 2,0 OFF : 3,5 TIME: 10s Pumps Off</p>	<p>The power supply is on. No pump is on. Mode is not known. The current pressure is 0.5 bar.</p>
<p>02,5 ON : 2,0 OFF : 3,5 TIME: 10s Pressure mode on</p>	<p>The power supply is on. Pump is turned on. Pressure switch mode is selected.. The current pressure is 2.5 bar.</p>
<p>02,5 ON : 2,8 OFF : 3,0 TIME: 10s Dynamic mode on</p>	<p>The power supply is on. Pump is turned on. Dynamic switch mode is selected. The current pressure is 2.5 bar.</p>
<p>07,5 ON : 2,0 OFF : 3,5 TIME: 10s Hand-P1 Hand-P2</p>	<p>The power supply is on. Pump 1 or Pump 2 or both are turned on manually The current pressure is 7.5 bar.</p>
<p>00,5 ON : 2,0 OFF : 3,5 TIME: 10s Extern Off</p>	<p>The power supply is on. Pump or pumps are turned off externally. Float switch is open or missing from pressure. The current pressure is 0.5 bar.</p>

## 9. Error messages

### 9.1 Error messages on the display of the EDS-2

In case of trouble off the pressure switch from module and the pump is running independently. The error message is displayed in plain text display.

**Fault can be reset by driving the external input "Reset".**

**Fault message, pressing the reset button to reset!**



<div>00,0</div> <div>Auto P1 Auto P2 Error</div> <div>Open Transducer</div>	<p>The power supply is on. Pump or pumps are turned off. The Transducer connection is open! The current pressure is not known.</p>
<div>00,5</div> <div>Auto P1 Auto P2 Error</div> <div>Low Water</div>	<p>The power supply is on. Pump or pumps are turned off. Electronic low water protection is active! The current pressure is 0.5 bar.</p>
<div>00,4</div> <div>Auto P1 Auto P2 Error</div> <div>Dry Run</div>	<p>The power supply is on. Pump or pumps are turned off. Electronic dry run protection is active! The current pressure is 0.4 bar.</p>
<div>10,5</div> <div>Auto P1 Auto P2 Error</div> <div>Defect Transducer</div>	<p>The power supply is on. Pump or pumps are turned off. The Transducer is defective! The current pressure is not known.</p>
<div>00,5</div> <div>ON : 2,0 OFF : 3,5 TIME: 10s</div> <div>Trip-P1 Trip-P2</div>	<p>The power supply is on. Pump or pumps are turned off. The motor protection has tripped. The current pressure is 0.5 bar.</p>
<div>00,5</div> <div>Auto P1 Auto P2 Error</div> <div>Error Switching</div>	<p>The power supply is on. Pump or pumps are turned off. Too many Switching (&gt; 30 / 60) per hour. The current pressure is 0.5 bar.</p>
<div>00,5</div> <div>ON : 5,0 OFF : 3,5 TIME: 10s</div> <div>Wrong Setting</div>	<p>The power supply is on. Pump or pumps are turned off. The pressure "ON" is higher than the pressure, "OFF".</p>

## **9.2 Troubleshooting**

### ***Monitor is dark***

Utility power and turned on?

If one or more fuses are broken?

### ***Pump does not start***

The start command is not!

Selector switch is on center position!

Fuses of the load circuit test!

### ***Pump does not start, even though "Auto" signal appears on the display***

Sensor is not connected? (Message: "Sensor Error")

The actual pressure is reached, or cut-out?

The pressure switch „On“ is set too small?

### ***Pump does not stop***

If the „Off“ pressure set too high (pump creating the pressure does not)?

If the off threshold is set too low?

If the pipeline of the system is not vented properly?

Back flow preventer installed not in the pressure line from the sensor?

If the check valve leaking?

In short, rigid piping, expansion tank installed in the discharge line downstream of the back flow preventer (check the pre-press pressure: start pressure - 0.5 bar)!

### ***Pressure monitor does not show the right pressure***

Factor for “transducer type” is wrong (e.g., 10 bar - Sensor, 25 bar - sensor)?

Transducer plug is wet?

Transducer cable is faulty?

### ***Soft starter is too warm***

Check ambient temperature! If necessary. they cool!

Reduce switching frequency!

### ***Pump switches on and off quickly***

Reduce switching frequency!

Check the expansion tank air buffer

### ***Display shows no data and pumps do not start***

EDS-2 module is defective.

Control fuse in the EDS-2 check.

## **10. Expert mode**

### **10.1 Dry run protection**

If the internal slide switch set to "**dry run**", the pump (s) monitored at all times in automatic or hand mode to "**dry run**". The pump (s) are stopped when the system pressure of 0.5 bar in 60 seconds is not reached.

### **10.2 Electronic low water protection**

The electronic "water protection" is a pressure monitoring. You to monitor the system pressure in automatic below. The pressure monitoring will be active after the fill mode. The fill mode is active again after every interruption. The system pressure falls below the switch pressure „On“ by 50% for longer than 3 minutes, off the system.

### **10.1 Pump change**

Which of the pump first starts up, is not defined. To ensure smooth operation of the pumps, all operating cycles or at least every 24 hours, the master / slave - changed operation. If a pump is stopped or fails due to a defect, the master will switch status.

### **10.2 Forced pump change**

Opening external release contact is changed, the master and slave. Now can be treated in the same way with the new master.

### 10.3 Dynamic Operation Mode (DY)

The mode "DY" provides for the safe shutdown output "0 " during operation of the pump system **without the expansion tank** or a very small expansion tank..

**In the mode "DY" turns the pump on the pressure (!) and off to output "0 "!**



Using the rotary switches **A**, text "ON", set the starting pressure of 0-100%. You should adjust the pressure „On“ switch as low as possible.

The rotary switch **B**, text "OFF", set the sensitivity (!) of the switch-off between 0-10%. The pressure-Off with the switch-off form a mathematical combination.

The logic of the mathematical combination is:

**Off pressure = measured pressure measurement cut-up time + - = Switch-off standby.**

Off The pressure is calculated after each switching cycle On / Off "again (!).

The rotary switch **T**, text "TIME", set the delay time between 5 sec and 30 sec, to the output "0" off point to reach safely.

The mode "DY" requires some experience in recruiting and detailed knowledge of the operation of the pump controller. If the system working satisfactorily, please contact a dealer or manufacturer.



Notice!

**This setting trace across the display.  
To set the switch-off knowledge is required!**

```

05,6  ON   :   2,0
      OFF  :   5,5
      TIME:  10s
Dynamic mode on
  
```

### 10.4 Reset the operating hours

A reset operation hours for the customer not planned!

To reset the operating hours to **00000**, the following procedure:

The reset button on the display. During the startup screen appears briefly put the clamp 28 on the EDS-2 to ground terminal 36. Reset is done!

It appears this message on the display:

```

RESET

0 RH      0 RH
  
```

### 10.5 Self-test the EDS-2 module

A self-test of the EDS-2 module is not intended for the customer!

To test the EDS-2 module, the following procedure:

The terminal 28 to ground 36 firmly connect. Mains supply. The EDS-2 responds with: Start self-test. The display changes to show self-test. The reset button on the Display button to cancel the self-test or end.

It appears this message on the display:

```


Self-test

aAbBcCdDeEfFgGhHiIhH
  
```


## 11. Technical data

### 11.1 Modes in the EDS-2 set:

After the opening of the EDS2 can be connected to the internal switch block set different operating modes:



Switch block inside:



Transducer 10 bar	/	Transducer 25 bar
Limit Funktion Modus	/	pressure switch modus
English	/	Deutsch
Dry Run off	/	Dry Run on

### 11.2 Technical data EDS-2

Supply voltage 230 VAC, max. 5 W  
 Sensor connection UB: 24VDC, S: 4 to 20 mA, 70 mA max.  
 Relay 3 x floating 230VAC 1A (6A)  
 Pressure range: 0 .. 100% of sensor value, follow-up time: 0-100%  
 Ambient temperature +5 ... +40 ° C  
 View LCD text display illuminated  
 IP 54 (according to the cabinet design)

The cabinet dimensions are different depending on the version and need to be asked separately.

## 12. Customer Settings

Customer Settings from:

Pressure On	A	_____ bar
Pressure Off	B	_____ bar
Run On Time	T	_____ sec
Switch 1 ON / OFF	1+2 / 1-2	_____
Switch 2 ON / OFF	Alarm / OFF	_____
Switch 3 ON / OFF	Test / OFF	_____
Switch 4 ON / OFF	DS / DY	_____
Locking	Yes / No	_____

Date: \_\_\_\_\_ from: \_\_\_\_\_